



**UNIDADES INTERIORES**

RAV-RM561BTP-E RAV-RM1101BTP-E  
RAV-RM801BTP-E RAV-RM1401BTP-E  
RAV-RM901BTP-E RAV-RM1601BTP-E



**UNIDADES EXTERIORES**

RAV-GM561ATP-E RAV-GM901ATP-E RAV-GM1101AT(8)P-E RAV-GM1601AT(8)P-E  
RAV-GM801ATP-E RAV-GM1401AT(8)P-E



**CONTROLES REMOTOS**

TCB-AX32E2 RBC-AMS55E-ES(EN)  
RBC-ASC11E RBC-AMT32E  
RBC-AS41E



SCOP MÁX.



4,60

CAPACIDAD



5kW > 14kW

FUNCIONAMIENTO



-15°C > +46°C

**SPA DI TRIFÁSICA**

**DIGITAL INVERTER**

Nombre Comercial		Spa DI Trifásica 110	Spa DI Trifásica 140	Spa DI Trifásica 160
<b>Capacidad de refrigeración</b>	kW	9,5	12,1	14,0
Rango de refrigeración (Mín. - Máx.)	kW	3,0 - 11,2	3,0 - 13,2	3,0 - 16,0
Consumo Nom. <Mín. - Máx.>	kW	3,0	4,4	5,1
EER	kW/kW	3,18	2,74	2,73
SEER	kW/kW	5,28	5,36	5,30
Clase Energética		A	-	-
Consumo estacional anual	kWh/año	629	-	-
<b>Capacidad de calefacción</b>	kW	11,2	13,0	16,0
Rango de calefacción (Mín. - Máx.)	kW	3,0 - 13,0	3,0 - 16,0	3,0 - 18,0
Consumo Nom. <Mín. - Máx.>	kW	3,0	3,5	4,7
COP	kW/kW	3,75	3,74	3,41
SCOP	kW/kW	4,19	4,19	3,90
Clase Energética		A+	-	-
Consumo estacional anual	kWh/año	2.537	-	-
<b>Unidad Interior</b>		<b>RAV-RM1101BTP-E</b>	<b>RAV-RM1401BTP-E</b>	<b>RAV-RM1601BTP-E</b>
Caudal de aire (A/B)	m³/h - l/s	2.100/1.500 - 583/417	2.100/1.500 - 583/417	2.100/1.500 - 583/417
Presión sonora (A/M/B)	dB(A)	40/36/33	40/36/33	40/36/33
Potencia sonora (A/M/B)	dB(A)	63/58/54	63/58/54	63/58/54
Dimensiones (Alt. x Anch. x Prof.)	mm	275 x 1.400 x 750	275 x 1.400 x 750	275 x 1.400 x 750
Peso	kg	40	40	40
Presión estática externa Fáb. <Mín. - Máx.>	Pa	50 <30 - 120>	50 <30 - 120>	50 <30 - 120>
<b>Unidad Exterior</b>		<b>RAV-GM1101AT8P-E</b>	<b>RAV-GM1401AT8P-E</b>	<b>RAV-GM1601AT8P-E</b>
Caudal de aire	m³/h - l/s	4.080 - 1.133	4.200 - 1.167	6.900 - 1.917
Presión sonora Ref / Cal	dB(A)	54 / 57	55 / 57	53 / 56
Dimensiones (Alt. x Anch. x Prof.)	mm	890 x 900 x 320	890 x 900 x 320	1.340 x 900 x 320
Peso	kg	69	69	94
Máxima corriente en arranque (MCA)	A	14,1	14,1	16,1
Conexiones (Gas / Líquido)	pulgadas	5/8" - 3/8"	5/8" - 3/8"	5/8" - 3/8"
Longitud de tuberías Nom. <Mín. - Máx.>	m	7,5 <5 - 50>	7,5 <5 - 50>	7,5 <5 - 50>
Diferencia máxima de altura	m	30	30	30
Longitud de tubería precargada	m	30	30	30
Carga adicional	g/m	35	35	0
Rango de operación (Refrigeración/Calefacción)	°C	-15 ~ 46 / -15 ~ 15	-15 ~ 46 / -15 ~ 15	-15 ~ 46 / -15 ~ 15
Refrigerante	kg	2,1	2,1	2,4

Precio de lista	Unidad Interior	€	<b>988</b>	<b>1.154</b>	<b>1.396</b>
	Unidad Exterior	€	<b>2.180</b>	<b>2.660</b>	<b>3.245</b>
	Mando (RBC-ASC11E)	€	<b>68</b>	<b>68</b>	<b>68</b>
	Conjunto	€	<b>3.236</b>	<b>3.882</b>	<b>4.709</b>